

Report No.: 56.05523 PURE Downlight

Test Time: 2023-06-03 20:37

Luminaire Property

Luminaire Category: Bridgelux V6HD 3000K CRI90

Luminaire Description: 48D

Current: 0.032 A

Power Factor: 0.902

Voltage: 225.8 V

Power: 6.60 W

Photometric Results

CIE Class: Direct

Measurement Flux: 249.2 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H48.4

Vertical Diffuse Angle(50%): V48.4

Luminaire Efficacy Rating (LER): 38

Max. Intensity: 338.67 cd

Total Rated Lamp Lumens: 249.2 lm


Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 338.66 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 339 cd

(10%):	34 cd	(16%):	54 cd
(25%):	85 cd	(40%):	135 cd
(63%):	213 cd	(100%):	339 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m Max Lux(100%): 3 lx			
— (1%):	0 lx	— (2%):	0 lx
— (5%):	0 lx	— (10%):	0 lx
— (20%):	1 lx	— (50%):	2 lx
— (100%):	3 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 339

(1%): 3 lx	(2%): 7 lx
(5%): 17 lx	(10%): 34 lx
(20%): 68 lx	(50%): 169 lx
(100%): 339 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°): 0.0-90.0: 5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

Zonal Lumen

[illegible]

Inspector:

Candlepower Table

Unit: cd

[illegible]

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector: