

Report No.: 81.11311 LENS Pendant Light Test Time: 2023-06-15 15:32

Luminaire Property

Luminaire Category: Bridgelux V10B 3000K,CRI90
Luminaire Description: 40D
Current: 0.098 A
Power Factor: 0.951
Voltage: 210.7 V
Power: 19.70 W


Photometric Results

CIE Class: Direct
Measurement Flux: 1425.9 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(50%): H38.9
Vertical Diffuse Angle(50%): V38.9
Luminaire Efficacy Rating (LER): 72
Max. Intensity: 3059.24 cd


Total Rated Lamp Lumens: 1425.9 lm
Efficiency: 100%
Upward Ratio: 0%

Central Intensity: 2995.18 cd
Pos of Max. Intensity: H0 V5

Picture Of Luminaire



Luminous Intensity Distribution Curve




— C0-C180 — C90-C270 — G5

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 3059 cd

(10%): 306 cd	(16%): 489 cd
(25%): 765 cd	(40%): 1224 cd
(63%): 1927 cd	(100%): 3059 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10m Max Lux(100%): 30 lx			
— (1%):	0 lx	— (2%):	1 lx
— (5%):	2 lx	— (10%):	3 lx
— (20%):	6 lx	— (50%):	15 lx
— (100%):	30 lx		


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 2995

(1%): 30 lx	(2%): 60 lx
(5%): 150 lx	(10%): 300 lx
(20%): 599 lx	(50%): 1498 lx
(100%): 2995 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Zonal Lumen

[illegible]

Inspector:

Candlepower Table

Unit: cd

[illegible]

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0

Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector: