

Report No.: 52.07521 UTH Down Light

Test Time: 2023-10-12 18:12

Luminaire Property

Luminaire Category: Bridgelux V6 3000K CRI90

Voltage: 229.7 V

Current: 0.069 A

Power: 8.60 W

Power Factor: 0.540

Photometric Results

CIE Class: Direct

Measurement Flux: 684.5 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H35.8

Vertical Diffuse Angle(50%): V35.8

Luminaire Efficacy Rating (LER): 80

Max. Intensity: 1741.72 cd

Total Rated Lamp Lumens: 684.5 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 1703.19 cd

Pos of Max. Intensity: H0 V5

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G5

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 1742 cd

(10%): 174 cd	(16%): 279 cd
(25%): 435 cd	(40%): 697 cd
(63%): 1097 cd	(100%): 1742 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot




Mounting Height: 10m		Max Lux(100%): 17 lx	
(1%):	0 lx	(2%):	0 lx
(5%):	1 lx	(10%):	2 lx
(20%):	3 lx	(50%):	9 lx
(100%):	17 lx		


C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 1703	
(1%): 17 lx	(2%): 34 lx
(5%): 85 lx	(10%): 170 lx
(20%): 341 lx	(50%): 852 lx
(100%): 1703 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Unit: cd

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector: