


32.08416 Action Track lighting Flexible chain leg



	_
259 170 45-125	
 ↓ ↓ Ø84 	

Connected Load	41W	Light Bea	am Talbe
Colour Temperature	2700/3000/3500/4000K	h(m)	E(lx)
Colour Rendition Index	CRI 90		
Optics	LENS	1.0 2.0	25672 6418
Beam Angle	19D/24D/38D/52D	3.0	2852
Track Phases	1 Circuit/ 3 Circuit	4.0	1605
Light Distribution	Action Flexible chain leg	5.0	1027
Luminous Flux Of The Luminaire	5001lm	This series uses ou fixture body, fast h dissipation, can be	
Luminaire Efficacy	119lm/W		
Colour Deviation	SDCM<5		er wattag e 3 versior
Light Source	LED	· · · ·	ne piece o exible cha
LED Type	СОВ	with gea	r box mod
Dimming Method	Triac/1-10V/ Dali		e needs of exible cha
Cover Material	Aluminum	5	sed for de ; with gea
Body Material	Aluminum		, j
IP Rating	IP20		
Housing Colour	Sandy White/ Sandy Black		
Weight	1.3kg		
Technical Region	220-240V 50/60Hz		



h(m)	E(lx)	D(m)	
		24°	
1.0	25672	0.42	
2.0	6418	0.84	
3.0	2852	1.26	
4.0	1605	1.68	
5.0	1027	2.11	
This series uses our patented			

fixture body, fast heat dissipation, can be small size and higher wattage. There are 3 versions of this series, one piece ordinary model, flexible chain leg, and with gear box model, to meet the needs of different places, flexible chain leg is mainly used for deeper space with blot, with gear box