

Report No.: 81.05511 FOS Pendant Light Test Time: 2023-09-19 16:44

Luminaire Property

Luminaire Category: Bridgelux V10A F90 3000K CRI90
Voltage: 221.4 V Current: 0.133 A
Power: 16.00 W Power Factor: 0.539


Photometric Results

CIE Class: Direct
Measurement Flux: 1811.9 lm
Downward Ratio: 100%
Horizontal Diffuse Angle(50%): H41.3
Vertical Diffuse Angle(50%): V41.3
Luminaire Efficacy Rating (LER): 113
Max. Intensity: 3901.14 cd


Total Rated Lamp Lumens: 1811.9 lm
Efficiency: 100%
Upward Ratio: 0%

Central Intensity: 3860.62 cd
Pos of Max. Intensity: H180 V5

Picture Of Luminaire



Luminous Intensity Distribution Curve





— C0-C180 — C90-C270 — G5

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 3901 cd

(10%): 390 cd	(16%): 624 cd
(25%): 975 cd	(40%): 1560 cd
(63%): 2458 cd	(100%): 3901 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m		Max Lux(100%): 39 lx	
(1%):	0 lx	(2%):	1 lx
(5%):	2 lx	(10%):	4 lx
(20%):	8 lx	(50%):	19 lx
(100%):	39 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 3861

(1%): 39 lx	(2%): 77 lx
(5%): 193 lx	(10%): 386 lx
(20%): 772 lx	(50%): 1930 lx
(100%): 3861 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Unit: cd

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector: