

Report No.: 32.05522 SPECTRUM Tracklight Test Time: 2023-09-13 17:00

## Luminaire Property

Luminaire Category: Bridgelux V8 3000K CRI90

Voltage: 223.2 V

Current: 0.116 A

Power: 14.20 W

Power Factor: 0.545

## Photometric Results

CIE Class: Direct

Measurement Flux: 1244.5 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H27.9

Vertical Diffuse Angle(50%): V27.9

Luminaire Efficacy Rating (LER): 88

Max. Intensity: 5048.9 cd

Total Rated Lamp Lumens: 1244.5 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 5048.89 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

## Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

## Isocandela (rectangle)



Imax (100%): 5049 cd

( 10%): 505 cd	( 16%): 808 cd
( 25%): 1262 cd	( 40%): 2020 cd
( 63%): 3181 cd	(100%): 5049 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

## IsoLux Plot




Mounting Height: 10m    Max Lux(100%): 50 lx

( 1%):	1 lx	( 2%):	1 lx
( 5%):	3 lx	( 10%):	5 lx
( 20%):	10 lx	( 50%):	25 lx
(100%):	50 lx		


C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## Illuminance at a Distance



## Vertical IsoLux Plot




Lowest(m): 1m    Highest(m): 11    Max Lux: 5049

( 1%): 50 lx	( 2%): 101 lx
( 5%): 252 lx	( 10%): 505 lx
( 20%): 1010 lx	( 50%): 2524 lx
(100%): 5049 lx	

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:



## Unit: cd

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector: