

Report No.: 32.05522 SPECTRUM Tracklight Test Time: 2023-09-13 16:56

Luminaire Property

Luminaire Category: Bridgelux V8 3000K CRI90

Voltage: 224.9 V

Current: 0.116 A

Power: 14.30 W

Power Factor: 0.543

Photometric Results

CIE Class: Direct

Measurement Flux: 1228.8 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H17.1

Vertical Diffuse Angle(50%): V17.1

Luminaire Efficacy Rating (LER): 86

Max. Intensity: 9622.68 cd

Total Rated Lamp Lumens: 1228.8 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 9622.68 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 9623 cd

(10%): 962 cd	(16%): 1540 cd
(25%): 2406 cd	(40%): 3849 cd
(63%): 6062 cd	(100%): 9623 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m		Max Lux(100%): 96 lx	
(1%):	1 lx	(2%):	2 lx
(5%):	5 lx	(10%):	10 lx
(20%):	19 lx	(50%):	48 lx
(100%):	96 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot




Lowest(m): 1m Highest(m): 11 Max Lux: 9623

(1%): 96 lx	(2%): 192 lx
(5%): 481 lx	(10%): 962 lx
(20%): 1925 lx	(50%): 4811 lx
(100%): 9623 lx	

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Unit: cd

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector: