




81.05511 FOS Pendant Lighting



| | |
|--------------------------------|--------------------------|
| Light Distribution | FOS Pendant Lighting |
| Colour Temperature | 2700/3000/3500/4000K |
| Colour Rendition Index | CRI 90 |
| Optics | LENS |
| Beam Angle | 20D/32D/41D/49D |
| Installation method | Surface Mounted |
| Connected Load | 16W |
| Luminous Flux Of The Luminaire | 1871lm |
| Luminaire Efficacy | 117lm/W |
| Colour Deviation | SDCM <5 |
| Light Source | LED |
| LED Type | COB |
| Dimming Method | Triac/1-10V/ Dali |
| Cover Material | Aluminum |
| Body Material | Aluminum |
| IP Rating | IP20 |
| Housing Colour | Sandy White/ Sandy Black |
| Weight | 0.6Kg |
| Technical Region | 220-240V 50/60Hz |

Light Beam Table

| h(m) | E(lx) | D(m) |
|------|-------|------|
| | | 20° |
| 1.0 | 10201 | 0.36 |
| 2.0 | 2550 | 0.72 |
| 3.0 | 1133 | 1.08 |
| 4.0 | 637 | 1.45 |
| 5.0 | 408 | 1.81 |

Application areas: retail, museums, hospitality, residential, offices and lobbies.