


51.07518 slim fixed recessed downlight



125	

Light Distribution	Slim Recessed Downlight	Light Be
Colour Temperature	2700/3000/3500/4000K	H(M)
Colour Rendition Index	CRI 90	
Optics	LENS	1.0 2.0
Beam Angle	21D/31D/40D/50D	3.0
Cut out	75mm	4.0
Connected Load	25W	5.0
Luminous Flux Of The Luminaire	2795lm	Small siz
Luminaire Efficacy	111lm/W	power. Have fixe
Colour Deviation	SDCM<5	versions, have 4 si
Light Source	LED	selected meet all
LED Type	СОВ	With ant
Dimming Method	Triac/1-10V/ Dali	a comfor environn
Cover Material	Aluminum	
Body Material	Aluminum	
IP Rating	IP20	
Housing Colour	Sandy White/ Sandy Black	
Weight	0.5Kg	
Technical Region	220-240V 50/60Hz	



H(M)	E(lx)	D(M)
		31°
1.0	9869.85	0.56
2.0	2467.46	1.11
3.0	1096.65	1.67
4.0	616.87	2.23
5.0	394.79	2.78

Small sizes but can be high power. Have fixed and adjustable 2 versions, each version have 4 sizes and 4 power for selected, can almost meet all the requirements. With anti-glare reflector, created a comfortable environment.