

Report No.: 93.05517 Suspension Light

Test Time: 2023-09-28 15:16

## Luminaire Property

Luminaire Category: Bridgelux V10 F90 4000K CRI90

Voltage: 224.8 V

Current: 0.112 A

Power: 24.20 W

Power Factor: 0.964

## Photometric Results

CIE Class: Direct

Measurement Flux: 2615.7 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H31.4

Vertical Diffuse Angle(50%): V31.4

Luminaire Efficacy Rating (LER): 108

Max. Intensity: 8823.41 cd

Total Rated Lamp Lumens: 2615.7 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 8823.4 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


## Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## Isocandela (rectangle)



Imax (100%): 8823 cd

( 10%): 882 cd	( 16%): 1412 cd
( 25%): 2206 cd	( 40%): 3529 cd
( 63%): 5559 cd	(100%): 8823 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

## IsoLux Plot




Mounting Height: 10m		Max Lux(100%): 88 lx	
( 1%):	1 lx	( 2%):	2 lx
( 5%):	4 lx	( 10%):	9 lx
( 20%):	18 lx	( 50%):	44 lx
(100%):	88 lx		


C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## Illuminance at a Distance



## Vertical IsoLux Plot



Lowest(m): 1m    Highest(m): 11    Max Lux: 8823

( 1%): 88 lx	( 2%): 176 lx
( 5%): 441 lx	( 10%): 882 lx
( 20%): 1765 lx	( 50%): 4412 lx
(100%): 8823 lx	

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

## The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:



## Unit: cd

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector: