

## 51.03825 Mini Pro Recessed Downlight



2 Et a Et a	CUT-OUT: Ø38mm	60° 60° 30° 3322cd 30°
Light Distribution	Mini Pro Recessed Downlight	Light Beam Ta <b>bl</b> e
Colour Temperature	2700/3000/3500/4000K	H(m) E(lx) D(m)
Colour Rendition Index	CRI 90	22° 1.0 3322.93 0.39
Optics	Lens	2.0 830.73 0.77
Beam Angle	17D/22D/32D/45D	3.0 369.21 1.16 207.68 1.51
Cut Out	38mm	4.0 207.88 1.54 5.0 132.92 1.93
Connected Load	8W	
Luminous Flux Of The Luminaire	608lm	Mainly for spaces with restricted floor heights,
Luminaire Efficacy	76m/W	such as clothing shops, furniture shops and other brand boutiques, car displays, jewelry, star hotels, high-end clubs, museums, chain stores, brand sales halls, professional windows, counters and
Colour Deviation	SDCM<5	
Light Source	LED	
LED Type	СОВ	
Dimming Method	Triac/0-10V/ Dali	
Cover Material	Aluminum	other accent lighting
Body Material	Aluminum	places.
IP Rating	IP20	
Housing Colour	Matt White/ Matt Black	
Weight	0.2Kg	
Technical Region	220-240V 50/60Hz	